

Models		FRK03	FRK06	FRK10	Models		FRK13	FRK17	FRK21	FRK26	FRK32	FRK42
Carrier weight	<i>t</i>	3-9	6-13	9-17	Carrier weight	<i>t</i>	12-20	14-23	16-27	20-32	26-40	32-55
Weight	<i>kg</i>	330	570	1000	Weight	<i>kg</i>	1400	1650	2000	2400	3300	4200
Excavator oil flow capacity	<i>l/min</i>	30-70	60-100	70-110	Excavator oil flow capacity	<i>l/min</i>	110-160	140-200	180-230	200-300	300-350	350-400
Excavator working pressure	<i>bar</i>	280	320	320	Excavator working pressure	<i>bar</i>	350	350	350	350	350	350
360° Rotation	°	360°	360°	360°	360° Rotation	°	360°	360°	360°	360°	360°	360°
Rotation oil flow capacity	<i>l/min</i>	10-25	20-40	20-40	Rotation oil flow capacity	<i>l/min</i>	30-60	40-60	40-60	40-60	40-60	40-60
Rotation Pressure	<i>bar</i>	100	100	100	Rotation Pressure	<i>bar</i>	140	140	140	140	140	140
A	<i>mm</i>	1280	1450	1620	A	<i>mm</i>	1900	2000	2100	2300	2500	2700
B	<i>mm</i>	415	520	605	B	<i>mm</i>	655	720	780	880	1000	1100
Steel blade length	<i>mm</i>	120	120	160	Steel blade length	<i>mm</i>	160	200	200	200	200	250
F1	<i>t</i>	110	130	150	F1	<i>t</i>	190	195	220	250	370	505
F2	<i>t</i>	60	65	70	F2	<i>t</i>	120	120	120	140	225	285
F3	<i>t</i>	35	40	45	F3	<i>t</i>	60	65	70	85	125	146
Ø Max	<i>mm</i>	28	30	30	Ø Max	<i>mm</i>	40	40	50	55	60	65